



HB6K TERA-GLIDE

6,000 PSI Braided Isobaric High Abrasion Resistant Hose

Extremely high pressure compact two braid high abrasion resistant hydraulic hose providing superior flexibility and a significantly tighter minimum bend radius.



TECHNICAL DATA

Specifications	Meets or Exceeds ISO 18752 BC (-4) AC (-6)
Tube	Black, oil resistant synthetic rubber
Reinforcement	2 high tensile steel wire braids
Cover	TERA-GLIDE: Black, high abrasion resistant, synthetic rubber. Resistant to oil, ozone and to UV rays.
Temperature	-40°F to +212°F (-40°C to +100°C)

Industry Approvals MSHA, ABS, DNV, USCG

Fittings

Fittings Series	Hose Size	
	04	06
F2	✓	✓
F	F2 Fer	F2 Fer

I.D.			#	O.D.		Working Pressure		Burst Pressure		Bend Radius		Weight	
Dash	Inch	Dn	Part Number	Inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	Kg/mt
04	1/4	6	HB6K-4	0.52	13.2	6,100	420	24,400	1,680	1.77	45	0.20	0.30
06	3/8	10	HB6K-6	0.65	16.5	6,100	420	24,400	1,680	2.76	70	0.26	0.38