




F2



HB3K TERA-GLIDE

3,000 PSI Braided Isobaric High Abrasion Resistant Hose

Medium pressure compact one or two braid high abrasion resistant hydraulic hose providing superior flexibility and significantly tighter minimum bend radius.



TECHNICAL DATA

Specifications	Meets or Exceeds SAE 100R17, ISO 18752 BC
Tube	Black, oil resistant synthetic rubber
Reinforcement	1 high tensile steel wire braid up to dash size 8 with 2 high tensile steel wire braid from dash size 10 and above
Cover	TERA-GLIDE: Black, high abrasion resistant, synthetic rubber. Resistant to oil, ozone and to UV rays.
Temperature	-40°F to +212°F (-40°C to +100°C)
Industry Approvals	MSHA, ABS, DNV, USCG

Fittings

Fittings Series	Hose Size					
	04	06	08	10	12	16
F2	✓	✓	✓	✓	✓	✓
F4					✓	✓
F	F1 Fer	F1 Fer	F1 Fer	F2 Fer	F2 Fer	F2 Fer

I.D.			#	O.D.		Working Pressure		Burst Pressure		Bend Radius		Weight	
Dash	Inch	Dn		Inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	Kg/mt
04	1/4	6	HB3K-4	0.48	12.3	3,000	210	12,000	840	1.97	50	0.12	0.18
06	3/8	10	HB3K-6	0.63	15.9	3,000	210	12,000	840	2.56	65	0.18	0.27
08	1/2	12	HB3K-8	0.75	19.1	3,000	210	12,000	840	3.54	90	0.26	0.38
10	5/8	16	HB3K-10	0.94	23.9	3,000	210	12,000	840	3.94	100	0.43	0.64
12	3/4	19	HB3K-12	1.10	28.0	3,000	210	12,000	840	4.72	120	0.54	0.80
16	1	25	HB3K-16	1.39	35.3	3,000	210	12,000	840	5.91	150	0.77	1.15