



ENGINEERING & TECHNICAL DATA — Flex-Tube® PE-IC

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)	IAPMO TS 19 Temp Rating
.75	.07	.012	1.3	1.5:1	20	20	HOT
1	.08	.012	1.8	1.5:1	20	20	COLD
1.25	.12	.012	2	1.5:1	20	20	COLD
1.375	.14	.012	2.3	1.5:1	20	20	COLD
1.5	.15	.012	2.5	1.5:1	20	20	COLD

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight polyethylene copolymer hose with a rigid external polyethylene helix

Temperature Range: -40°F to 160°F*

Standard Color: Aqua with White Helix

Standard Lengths: 10 feet, custom lengths available up to 50 feet

- Meets IAPMO compliance

** See IAPMO TS 19 standard for RV drain/fill hose temperature & pressure requirements*

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY