



ENGINEERING & TECHNICAL DATA — Flexadux TR® E-7

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4	.44	.030	3.5	3:1	24	22
6	.73	.030	6	3:1	18	15
8	1	.030	8	3:1	12	7

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight polyethylene alloy hose with UV additive reinforced with a bronze coated spring steel wire helix

Temperature Range: -40°F to 160°F

Standard Color: Clear

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY