



ENGINEERING & TECHNICAL DATA — Flex-Tube® VR-U

INSIDE DIAMETER (IN)	OUTSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	3.47	.72	.050	5	28	40
4	4.53	1.1	.055	7	28	40

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Specially formulated static dissipative heavy weight UV resistant polyurethane hose reinforced with a UV resistant rigid external PVC left handed helix & an embedded copper braided grounding wire

Temperature Range: -40°F to 160°F (Application conditions will affect service temperature.)

Standard Color: Clear with Yellow Helix

Standard Lengths: 100 Feet

- Surface Resistivity Level: 10^8 - 10^{10} Ohms/Square
- For vapor use only – wire must be earth grounded less than 10 Ohms per applicable regulations.

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY