



ENGINEERING & TECHNICAL DATA — Springflex® FX-180 DF

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
12	.8	N/A	N/A	N/A	N/A	6
16	1	N/A	N/A	N/A	N/A	4
20	1.1	N/A	N/A	N/A	N/A	2.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: High strength sewn single-ply PVC vinyl coated polyester fabric duct with 3" holes positioned upon request

Temperature Range: -20°F to 180°F

Standard Color: White

Standard Lengths: 25, 50, 75 & 100 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY